

DECOLUX B IP65 NRG WL/CL Safety Luminaire

Part No. L18183

Categories: NRG Luminaires, NRG Luminaires, NRG+ CPS, NRG+ LPS

Tag: DECOLUX IP65 WL/CL



exilux



Safety wall and ceiling luminaire IP65 for outdoor and indoor use.

TECHNICAL SPECIFICATION

Weight	1.3 kg
System	NRG
Insulation class	II
Compliance	CE, UKCA
IP rating	IP65
IK rating	IK10
EN 1838	EN 1838
Glow wire test	850 °C – 30s
Mounting luminaire	Surface ceiling, Surface wall
Nominal input voltage (V)	230 V 50/60 Hz – 220 V DC +25/-20 %
Nominal flux (lm)	2980 / 20 W – 4768 / 32 W Adjustable
Polar curve image	YES
Power consumption AC (VA)	21 – 33
Power consumption DC (mA / W)	92 / 20 W – 148 / 32 W Adjustable
Colour temperature (°K)	3000 – 4000 Adjustable
Service life L80B20	50000
Colour	RAL 9003
Material	PC
Operating temperature (°C)	-20 to +50



PRODUCT ACCESSORIES



LA18066
DECOLUX Decorative
White Ring B



LA18067
DECOLUX Decorative
Black Ring B