

DECOLUX B IP65 NRG ZB WL/CL 3H

Safety Luminaire

Part No. L21035

Categories: Luminaires, NRG ZB Wireless

Tag: DECOLUX IP65 WL/CL



exilux



Safety wall and ceiling luminaire IP65 for outdoor and indoor use.

TECHNICAL SPECIFICATION

Weight	1.8 kg
System	NRG ZB Wireless
Insulation class	I
Compliance	CE, UKCA
IP rating	IP65
IK rating	IK10
EN 1838	EN 1838
Glow wire test	850 °C – 30s
Mounting luminaire	Surface ceiling, Surface wall
Warranty	5 Years, 10 Years
Nominal input voltage (V)	230 V 50/60 Hz
Emergency duration (h)	3
Battery	LiFePO4 6.4 V 6.4 Ah
Nominal flux (lm)	2980 / 26 W – 4768 / 38 W M Adjustable – 740 NM
Polar curve image	YES
Power consumption AC (W)	Max. 26 W – 38 W Adjustable
Charging times (h)	24
Mode of operation	Maintained, Non-maintained
Colour temperature (°K)	3000 – 4000 Adjustable
Service life L80B20	50000
Colour	RAL 9003
Operating temperature (°C)	-20 to +50



PRODUCT ACCESSORIES



LA18066
DECOLUX Decorative
White Ring B



LA18067
DECOLUX Decorative
Black Ring B