

# DECOLUX B MS IP65 NRG+ WL/CL Safety Luminaire

Part No. L18186

Categories: NRG+ CPS, NRG+ LPS, NRG+ Luminaires, NRG+ Luminaires

Tag: DECOLUX IP65 WL/CL



**exilux**



Safety wall and ceiling luminaire IP65 for outdoor and indoor use.

## TECHNICAL SPECIFICATION

|                               |                                      |
|-------------------------------|--------------------------------------|
| Weight                        | 1.3 kg                               |
| System                        | NRG+                                 |
| Insulation class              | II                                   |
| Compliance                    | CE, UKCA                             |
| IP rating                     | IP65                                 |
| IK rating                     | IK10                                 |
| EN 1838                       | EN 1838                              |
| Glow wire test                | 850 °C – 30s                         |
| Mounting luminaire            | Surface ceiling, Surface wall        |
| Nominal input voltage (V)     | 230 V 50/60 Hz – 220 V DC +25/-20 %  |
| Nominal flux (lm)             | 2980 / 20 W – 4768 / 32 W Adjustable |
| Polar curve image             | YES                                  |
| Power consumption AC (VA)     | 21 – 33                              |
| Power consumption DC (mA / W) | 92 / 20 W – 148 / 32 W Adjustable    |
| Colour temperature (°K)       | 3000 – 4000 Adjustable               |
| Service life L80B20           | 50000                                |
| Colour                        | RAL 9003                             |
| Material                      | PC                                   |
| Operating temperature (°C)    | -20 to +50                           |



## PRODUCT ACCESSORIES



LA18066  
DECOLUX Decorative  
White Ring B



LA18067  
DECOLUX Decorative  
Black Ring B