

# DECOLUX B MS IP65 NRG WL/CL Safety Luminaire

Part No. L18185

Categories: NRG Luminaires, NRG Luminaires, NRG+ CPS, NRG+ LPS

Tag: DECOLUX IP65 WL/CL







Safety wall and ceiling luminaire IP65 for outdoor and indoor use.

## TECHNICAL SPECIFICATION

Weight	1.3 kg
System	NRG
Insulation class	II
Compliance	CE, UKCA
IP rating	IP65
IK rating	IK10
EN 1838	EN 1838
Glow wire test	850 °C – 30s
Mounting luminaire	Surface ceiling, Surface wall
Nominal input voltage (V)	230 V 50/60 Hz – 220 V DC +25/-20 %
Nominal flux (lm)	2980 / 20 W – 4768 / 32 W Adjustable
Polar curve image	YES
Power consumption AC (VA)	21 – 33
Power consumption DC (mA / W)	92 / 20 W – 148 / 32 W Adjustable
Colour temperature (°K)	3000 – 4000 Adjustable
Service life L80B20	50000
Colour	RAL 9003
Material	PC
Operating temperature (°C)	-20 to +50



## PRODUCT ACCESSORIES



LA18066  
DECOLUX Decorative  
White Ring B



LA18067  
DECOLUX Decorative  
Black Ring B