

DECOLUX M MS IP65 NRG+ WL/CL Safety Luminaire

Part No. L18182

Categories: NRG+ CPS, NRG+ LPS, NRG+ Luminaires, NRG+ Luminaires



Tag: DECOLUX IP65 WL/CL



Safety wall and ceiling luminaire IP65 for outdoor and indoor use.

TECHNICAL SPECIFICATION

Weight	0.96 kg
System	NRG+
Insulation class	II
Compliance	CE, UKCA
IP rating	IP65
IK rating	IK10
EN 1838	EN 1838
Glow wire test	850 °C – 30s
Mounting luminaire	Surface ceiling, Surface wall
Polar curve image	YES
Power consumption AC (VA)	14 – 23
Nominal input voltage (V)	230 V 50/60 Hz – 220 V DC +25/-20 %
Nominal flux (lm)	1937 / 13 W – 3278 / 22 W Adjustable
Power consumption DC (mA / W)	60 / 13 W – 102 / 22 W Adjustable
Colour temperature (°K)	3000 – 4000 Adjustable
Service life L80B20	50000
Colour	RAL 9003
Material	PC
Operating temperature (°C)	-20 to +50



PRODUCT ACCESSORIES



LA18064
DECOLUX Decorative
White Ring M



LA18065
DECOLUX Decorative
Black Ring M