

# DECOLUX M MS IP65 NRG WL/CL

## Safety Luminaire

Part No. L18181

Categories: NRG Luminaires, NRG Luminaires, NRG+ CPS, NRG+ LPS

Tag: DECOLUX IP65 WL/CL

**exilux**

NRG



IP65

IK10

EN 1838



GWT 850°C



Safety wall and ceiling luminaire IP65 for outdoor and indoor use.

### TECHNICAL SPECIFICATION

|                               |                                      |
|-------------------------------|--------------------------------------|
| Weight                        | 0.96 kg                              |
| System                        | NRG                                  |
| Insulation class              | II                                   |
| Compliance                    | CE, UKCA                             |
| IP rating                     | IP65                                 |
| IK rating                     | IK10                                 |
| EN 1838                       | EN 1838                              |
| Glow wire test                | 850 °C – 30s                         |
| Mounting luminaire            | Surface ceiling, Surface wall        |
| Nominal input voltage (V)     | 230 V 50/60 Hz – 220 V DC +25/-20 %  |
| Nominal flux (lm)             | 1937 / 13 W – 3278 / 22 W Adjustable |
| Polar curve image             | YES                                  |
| Power consumption AC (VA)     | 14 – 23                              |
| Power consumption DC (mA / W) | 60 / 13 W – 102 / 22 W Adjustable    |
| Colour temperature (°K)       | 3000 – 4000 Adjustable               |
| Service life L80B20           | 50000                                |
| Colour                        | RAL 9003                             |
| Material                      | PC                                   |
| Operating temperature (°C)    | -20 to +50                           |



PRODUCT ACCESSORIES



LA18064  
DECOLUX Decorative  
White Ring M



LA18065  
DECOLUX Decorative  
Black Ring M