

MULTYLUX 24m NRG BUS WL/CL 3H

Exit Sign Luminaire

Part No. L20022

Categories: Exit Signs, NRG BUS

Tag: MULTYLUX WL/CL



exilux



Exit sign luminaire suitable for mounting on walls, ceilings and recessed.

TECHNICAL SPECIFICATION

Weight	1 kg
Nominal input voltage (V)	230 V 50/60 Hz
System	NRG BUS DALI 2
Insulation class	II
Compliance	CE, UKCA
IP rating	IP42
IK rating	IK04
Glow wire test	850 °C – 30s
Mounting exit sign	Recessed ceiling, Recessed wall, Surface ceiling, Surface wall, Suspended ceiling
Warranty	5 Years, 10 Years
Charging times (h)	24
Mode of operation	Maintained, Non-maintained
Battery	LiFePO4 3.2 V 4.5 Ah
Emergency duration (h)	3
Power consumption AC (W)	Max. 7
Colour temperature (°K)	5700
Service life L80B20	50000
Colour	RAL 9003
Material	ALUMINIUM – PC
Operating temperature (°C)	0 to +45



PRODUCT ACCESSORIES



LA18051
MULTYLUX Recessed
Frame



LA18052
MULTYLUX Wiring
Suspension 0.5m Set



LA18053
MULTYLUX Wiring
Suspension 1m Set