MULTYLUX 32m NRG+ WL/CL Exit Sign Luminaire

Part No. L18154
Categories: NRG+ CPS, NRG+ Exit Signs, NRG+ Exit Signs, NRG+ LPS
Tag: MULTYLUX WL/CL

Exit sign luminaire suitable for mounting on walls, ceilings and recessed.

TECHNICAL SPECIFICATION

Weight	1.15 kg
System	NRG+
Insulation class	II
Compliance	CE, UKCA
IP rating	IP42
IK rating	IK04
Viewing distance	32 m
Glow wire test	850 °C – 30s
Mounting exit sign	Recessed ceiling, Recessed wall, Surface ceiling, Surface wall, Suspended ceiling
Nominal input voltage (V)	230 V 50/60 Hz – 220 V DC +25/-20 %
Power consumption AC (VA)	7
Power consumption DC (mA / W)	15 / 3.3
Colour temperature (°K)	5700
Service life L80B20	50000
Colour	RAL 9003
Material	ALUMINIUM – PC
Operating temperature (°C)	-10 to +40





PRODUCT ACCESSORIES

LA18051
MULTYLUX Recessed Frame

LA18052
MULTYLUX CEILING SUSPENSION SET

LA18053
MULTYLUX FRAME SUSPENSION 1.0M SET