

# NRG+ LPS 24-230-04 39AH Low Power Supply System

Part No. LPS16002

Categories: Control Systems, NRG+ LPS





Low Power Supply System (LPS) for emergency lighting. 230V AC/DC outgoing circuits with integrated monitoring and maintained and non-maintained functions.

User-friendly 7" Touchscreen-Display, integrated Modbus interface. Designed according to BS EN 50171, BS EN 62485-2, BS EN 62034.

## TECHNICAL SPECIFICATION

Weight	33.7 kg
Dimensions (D x W x H)	180 x 455 x 680 mm
Power consumption in standby mode (W)	30.5
System	NRG+
Insulation class	I
Compliance	CE, UKCA
IP rating	IP20
Mounting system	Surface wall
Nominal input voltage (V)	1~N/PE 230 V 50 Hz / 3~N/PE 400 V 50 Hz
Nominal output voltage (V)	230 VAC / 230 VDC ± 5 %
Outgoing circuits	0.87 A 200 W 4 circuits
Natural, technical ventilation	1.97 cm <sup>2</sup> – 0.07 m <sup>3</sup> /h
Autonomy and power according BS EN 50171	1 h max. 250 W – 3 h max. 165 W
Charging time (hours)	12
Colour	RAL 9016
Material	Galvanised and painted metal sheet
Interface	TCP / IP – MODBUS – USB
Cable entry	Above
Operating temperature (°C)	0 to +40
Battery temperature (°C)	+20 to +25
Battery	AGM-VRLA 6 x 13 Ah – 10 YEARS expected lifespan



## PRODUCT ACCESSORIES



CLA15005  
NRG+ ULM Addressable  
Module



CLA15000  
NRG+ BNW-S Mains  
Monitoring Module



CLA15009  
NRG+ BNW-Si-S Mains  
Monitoring Module



CLA15001  
NRG+ IOe24 Light Switch  
Query Module



CLA15002  
NRG+ IOe230-S Light  
Switch Query Module



CLA15003  
NRG+ Remote Panel  
BMT-V2 RC



CLA15004  
NRG+ Remote Panel  
BMT-V2 WL



CLA15008  
NRG+ PC Visualisation  
Software