

NRG+ SUB B20

Part No. S15004

Categories: NRG+ CPS, Substations

NRG+



CE

UK
CA

IP40



NRG + Sub for sub-distribution areas and system extensions.

230V AC/DC outgoing circuits with integrated monitoring and maintained and non-maintained functions.

Designed according to BS EN 50171, BS EN 62034.

TECHNICAL SPECIFICATION

Weight	15 kg
Dimensions (D x W x H)	140 x 324 x 674 mm
System	NRG+
Insulation class	I
Compliance	CE, UKCA
IP rating	IP40
Mounting system	Surface wall
Nominal input voltage (V)	1~N/PE 230 V 50 Hz
Nominal output voltage (V)	230 VAC / 216 VDC ± 15 %
Outgoing circuits	20 x 3 A 690 W
Colour	RAL 9016
Material	Galvanised and painted metal sheet
Operating temperature (°C)	0 to +40



PRODUCT ACCESSORIES



CLA15005
NRG+ ULM Addressable
Module



CLA15000
NRG+ BNW-S Mains
Monitoring Module



CLA15001
NRG+ IOe24 Light Switch
Query Module



CLA15002
NRG+ IOe230-S Light
Switch Query Module



CLA15009
NRG+ BNW-5i-S Mains
Monitoring Module