

# NRG+ SUB B48

Part No. S15011

Categories: NRG+ CPS, Substations





NRG + Sub for sub-distribution areas and system extensions.

230V AC/DC outgoing circuits with integrated monitoring and maintained and non-maintained functions.

Designed according to BS EN 50171, BS EN 62034.

## TECHNICAL SPECIFICATION

Weight	29 kg
Dimensions (D x W x H)	140 x 574 x 674 mm
System	NRG+
Insulation class	I
Compliance	CE, UKCA
IP rating	IP40
Mounting system	Surface wall
Nominal input voltage (V)	1~N/PE 230 V 50 Hz
Nominal output voltage (V)	230 VAC / 216 VDC ± 15 %
Outgoing circuits	48 x 3 A 690 W
Colour	RAL 9016
Material	Galvanised and painted metal sheet
Operating temperature (°C)	0 to +40



## PRODUCT ACCESSORIES



CLA15005  
NRG+ ULM Addressable  
Module



CLA15000  
NRG+ BNW-S Mains  
Monitoring Module



CLA15001  
NRG+ IOe24 Light Switch  
Query Module



CLA15002  
NRG+ IOe230-S Light  
Switch Query Module



CLA15009  
NRG+ BNW-5i-S Mains  
Monitoring Module

